



SEALINK SDN BHD(20471-D)

Tel : +60 85 651778, Fax : +60 85 652480, Email : seasb@po.jaring.my

Website: www.asiasealink.com

SEALINK VANESSA 3

48M UV HULL NO : SSS110



BASIC FUNCTION

- ✓ As Utility /supply vessel
- ✓ Offshore support
- ✓ General assistance

GENERAL

Year Built	Delivered in October 2004
Classification	American Bureau of Shipping (A1+ AMS for unrestricted services)
Port of Registry & Flag	Labuan, Malaysia
Official No./ Callsign	329881/ 9WEQ6
Builder :	Sealink Shipyard, Miri

MAIN DIMENSION

Length O.A	48.00 M
Beam	11.00 M
Depth	3.50 M
Designed Draft	2.50 M
Max Draft	2.80 M
Gross/Net Tonnage	496/149

TANK & LOADING CAPACITY (98% APPX)

Fuel Tanks	295m ³
Potable Water	313m ³
Deck Area	208 M ²
Deadweight	~575 Tonnes
Displacement	~1025.55 T Appx

CARGO HANDLING

F.O	75cum/hr @50m head
FW	75cum/hr @50m head

PERFORMANCE

Speed	12 knots design
-------	-----------------

Endurance 28 Days

MACHINERY

Main Engine	2 x 1200 BHP @ 1800 rpm CUMMINS c/w REINTJES gear box.
Generator	2 x 150 kW CUMMINS 415/3/50,
Bowthruster	3mt Schottel Tunnel thruster type Imput 294 HP CAT3406
Control	Fwd & aft

NAVIGATION AND COMMUNICATION

Complies with GMDSS A3 for vessel < 500 GRT
3 x VHF Radio , 1 x MF/HF Radio, 1 x INMARSAT C,
1 x Radar Furuno M-1940, 1 x Echo Sounder, 1 x GPS,
Magnetic compass & Autopilot , & sat compass, speed log, AIS

DECK MACHINERY & CONNECTIONS

Bow Anchor	2 x 900 kg Stockless anchor with 9 shackles anchor chain.
Electro Hydraulic Windlass	Twin Gypsy c/w 2 wrapping heads c/w hydraulic-electro power pack
Capstan	-2 x 5MT,
tugger winch	-2 x 5mt
stern roller,	
1 x crane of 2mt at 6m reach	
Reefer Point	6 Nos.
crash rail on main deck.	

SAFETY AND FIREFIGHTING EQUIPMENT

In compliance with Class requirement &/ requirement of Flag administration
Vessel comply to MARPOL 1 & IV, V
LSA is for 25-men complement.
1 x 6 men rescue boat (optional)
½ fifi 1200cum³/hr c/w 2 fire monitor + Dispersant system (optional)

ACCOMMODATIONS

Fully central airconditioned 22 berth



1 N B : Specification listed here are given in good faith and may be subject to changes on construction